



Address: No.78, XingYe Road, Chaolian Town, Jiangmen City, Guangdong, China. (Jiangmen Office)

Address: RM 1902 EASEY COMM BLDG 253-261 HENNESSY ROAD WANCHAI, HK (Hongkong Office)

Tel: +86 137 2595 7662 (Whatsapp) +86-750 3094316 Fax: +86 750 3723909

1000-2000 bottle/hour (500ml) Separated Washing & Filling & Capping Machine (Model: 12/12/1)



I Automatic bottle washer (CP-12)

CP series full-automatic rotary bottle washer adopts 1990's technology of West Germany SEN Corp, and is developed by combining the situation of our country. It adopts continuously spraying and washing way. It has high efficiency and good washing result. The equipment is applicable in different kinds of bottles. It's perfect equipment in the production line of beverage industry.

Main technical parameter:

Model	CP-12
Production capacity	2000-3000B/H
Power	0.75kw
Overall dimensions (mm)	1200×1200×1700
Weight	700kg

Equipment Picture:



Main components and materials:

Name	Type	QTY	Remark
Electromagnetic Speed Motor Controller	JDIA—40		DELIXI
Main stop switch	SAY7 11ZS	1Pcs	DELIXI
Start button	LAY7 11BN	2Pcs	DELIXI
Stop button	LAY7 11BN	2Pcs	DELIXI
3P breaker	DZ47—C25	1Pcs	DELIXI
1P breaker	DZ47—C10	2Pcs	DELIXI
AC contactor	CIX2—1810	2Pcs	DELIXI
Variable speed motor	Y80M—4,0.75	1set	
water pump	BJZ075	1set	
Worm reducer	WPO-80 40:1	1set	
Clip Material	stainless steel 304		
Material for turntable, watershed disk and fixed disk	stainless steel 304		
Sliding bearing	Harbin Bearing		
Overall dimension	1200×1200×1700(mm)		

II Automatic atmospheric pressure filler (CG-12)

The filler is mainly used for filling non-gas contained drinks such as purified water, mineral water and juice etc. You can use it for high temperature filling by replacing the parts. It is an ideal filling equipment of medium-small scale drink factory.

Main technical parameter

Model	CG-12
Production capacity	1000-2000B/H
Power	0.75 kw
Overall dimensions (mm)	1040×1040×1800
Weight	800kg

Equipment Picture:



Main components and materials:

Name	Type	QTY	Remark
Electromagnetic Speed Motor Controller	JDIA—40		DELIXI
Power light	AD16—22D/S 220V	2Pcs	DELIXI
Main stop switch	SAY7 (LA7) 11ZS	1Pcs	DELIXI

Start button	LAY7 11BN	2Pcs Blue	DELIXI
Stop button	LAY7 11BN	2Pcs Red	DELIXI
Push button	LAY7 20XB/31	1Pcs	
3P breaker	DZ47—C25	1Pcs	DELIXI
1P breaker	DZ47—C10	1Pcs	DELIXI
AC contactor	CIX2—1810	1Pcs	DELIXI
Variable speed motor	Y80M—4,0.75	1Pcs	0.75kw
water pump	BJZ075	1Pcs	
Worm reducer	WPO-80 40:1	1Pcs	
Material for Filling liquid cylinder and valve	Stainless steel 304		
Sliding bearing	Harbin Bearing, copper base bearing		
Material for guide rod, sleeve	Stainless steel AISL304		
Seals, nitrile rubber, silicone rubber			
Overall dimension	1040×1040×1800(mm)		

III Automatic sealer (FG-1)

The sealer is suitable for sealing various PET bottles. It is perfect in performance, reliable in operation and easy in maintenance. So it is widely used in automatic packing lines for various kinds of wine, drink, food, medicine, reagent, pesticide and so on. It is one of the most ideal screw type automatic sealing equipment.

Equipment Picture:





Main technical parameter:

Model	FG-1
Production capacity	1000-2000B/H
Power	0.75kw
Overall dimensions (mm)	940x700x2000
Weight	300kg

Main components and materials:

Name	Type	QTY	Remark
3 pole Button Switch	starter	2Pcs	DELIXI
Main motor	Y802-4	1Pcs	0.75KW
Drop cap motors	90CK60	1Pcs	90W
Material for main parts: Stainless steel 304			
Sliding bearing		Harbin Bearing	
Overall dimension	940x700x2000(mm)		

IV Conveying system (With platform)

Name	Type	QTY	Remark
Electromagnetic Speed Motor Controller	JDIA40	1Pcs	DELIXI
Push button	LAY7 20XB131	1Pcs	DELIXI
AC contactor	CJX2--0910		DELIXI
Variable speed motor	0.55KW 380V	1Pcs	Suzhou
Shell packaging board	Stainless steel 304		
Sliding bearing	Harbin Bearing		
Platform for bottle in and out		2set	Stainless steel 304

Pictures of the 3 in 1 water filling machine:

