



Address: No.78, XingYe Road, Chaolian Town, Jiangmen City, Guangdong, China. (Jiangmen Office)

Address: RM 1902 EASEY COMM BLDG 253-261 HENNESSY ROAD WANCHAI, HK (Hongkong Office)

Tel: +86 137 2595 7662 (Whatsapp) +86-750 3094316 Fax: +86 750 3723909

JMB-80A Semi Auto Shrink- Wrapping Machine



1. Scope of Application:

Auto shrink- wrapping machine series are suitable for the package of bottled water ,beverage、household、 electric appliances、 electrical units、 floor boards、 pottery and so on.

2. Feature:

- 1) It can make package perfect whatever it is without pallet, cartoon, rectangle, round or flat shape.
- 2) It has the advantage of less cost and better appearance.
- 3) Replace film conveniently. It has failure alarm, lock device, reliable running.
- 4) Automatic film feeding and cutting function, and the length of film for feeding and cutting is adjustable.
- 5) With stainless steel heating tube to ensure the high efficiency even heat, not easy to break and easy changing.
- 6) The whole machine applies super steel and stainless steel, with compact and durable structure. This new type of wrapping machine is the ideal equipment for beverage filling line.

3. Technical Diameter:

Machine Dimension	3950*750*1960(L*W*H.mm)
Max packed size	600*400*350(L*W*H.mm)
Shrinkage film material	PE、PP、PVC、POF
Shrinkage film thickness	0.03-0.15(mm)



Oven temperature	160 - 250°C
Heat Cutting Temperature	160 - 200°C
Max output	3-6Bag/Min.
Actual Power	15Kw/H.
Max power consumption	18KW
Voltage	AC 380V/220V,3Phs
Weight	750kg.
Applicable Internal Diameter of Paper Tube	5"~10".

4. Components List:

1. Automatic Film Mantling & Cutting Machine		
Item	Mole	Qty
Driving motor	YS5624;90w;220/380;50Hz	2
Gearing head	56B14;RV30;i=10	2
Cylinder	SC63x400	1
Double Shaft Cylinder	TN-φ20×30	1
Heating tube	φ11;L=650mm	1
Filters Rugulators lubricators	GL300-10	1
Timer	JSS48A	3
Temperature Controller	REX-C100	1
pilot light	AD Series	2
Starting switch	LA Series	4
Power Switch	2.1A/24V	1
Electric Relay	MY4NJ;24VDC ; OMRON	5
Solid State Relay	SSR-40DA	1
Proximity Switch	SC1204-N	3
Residual Current Circuit Breaker	C65L-32/4P	2
Pneumatic valve	4V210-08 Airtac	3
Fuse Holder	3A 8A	2
Dimension	1450x750x1960 (mm)	

2. Automatic Heat Shinking Machine		
Driving motor	YS8024;750w;220/380;50Hz	1
Turbine Gearbox	WPS60-60A	1
Heating tube	φ 16*1305 (1200W)	10
Temperature Controller	REX-C100	1
pilot light	AD Series	1
Starting switch	LA Series	5
Residual Current Circuit Breaker	380V/63A	1



Fuse Base	RT18-32	2
AC contactor	4010/220V;1210/220V	4
Cooling fan	220V,50w	4
Intermediate relay	MY2NJ-220/AC	2
Dimension	2500x750x1600 (mm)	

5 Packing Type:

a) 300-600ml: Big package: 4x6, 4x5; Small package: 3x4, 3x5.

b) 700-2000ml: Big package: 3x3, 3x4; Small package: 2x2, 2x3.

6 Picture:



